

## **Downlight Protection for a warmer home!**

Thermahood's unique design provides an airtight seal that prevents heat loss and allows for continuity of loft insulation.

### Thermahood - TH 120 M

#### Reduce heat loss!

Downlights add ambience and character to our homes. However, they are a weak point in fighting against heat loss as they can reduce the effectiveness of loft insulation by as much as 30%. Air leakage can be significantly reduced by fitting a Thermahood cover.

#### Improve air quality!

Using downlight covers can help minimise the risk of condensation by reducing draughts and airflow – our product works in tandem with heat recovery systems, supporting controlled airflow. Thermahood helps prevent insects from infiltrating living areas.

#### Reduce fire risk!

Thermahood is manufactured from recyclable, flame retardant material, which helps reduce the risk of fire from household storage items.

Meet requirements for Building Regulation 2.3: C2 condensation \* L1 fuel conservation \* E1 sound protection

#### **Ingress of Dust Test**

Thermahood was subjected to the test of ingress dust and was deemed to comply with the requirements for dust tight luminairies, i.e. ingress protection classification IP6X - Test Specification: BS EN 60598-1:2015

<u>Air Tightness Test</u> -Thermahood has been tested in compliance with Building Control Doc. F 'Conservation of Fuel and Power' and BS EN 1026: 2000 Window and Doors - Air permeability - test method. Thermahood reduced air leakage at 50pa from 5.97(m3/h\*m2) to 4.69(m3/h\*m2), an air-leakage reduction of 21.45% Test Ref. No. SRC 04/13 (AA17549A A. A. Testing)

Easy to install by anyone, once fitted, Thermahood doesn't require any maintenance. Please refer to fitting instructions for further information. Reduce noise Infiltration, Thermahood product provide a noise barrier.






Thermahood Ltd,
Starling House, 4 Slatemill Road,
Kilkeel, Newry, Co.Down, BT34 4JW
Tel: 028 4177 4047 www.thermahood.com
info@thermahood.com



# **Downlight Protection for a warmer home!**

Thermahood's unique design provides an airtight seal that prevents heat loss and allows for continuity of loft insulation.

Material	Mild Steel	Euro Class - A1
Material Finish	Zinc Plated	EN ISO19598 - specification Fe//Zn5//An/T0
Product Dimensions	285mm x 285mm	120mm high



Thermahood Ltd Starling House, 4 Slatemill Rd, Kilkeel, Newry, Co. Down, BT34 4JW